

Addresses

- [Create Address Endpoint](#)
- [Update Address Endpoint](#)
- [Delete Address Endpoint](#)

Create Address Endpoint

Structure

Name	Type	Description	Required
id	int	The id for the address	No
name	string	The name of the address	No
first_name	string	The first name for the address	Yes
last_name	string	The last name for the address	Yes
company	string	The company for the address	No
mobile	string	The mobile number for the address	No
phone	string	The phone number for the address	No
line_1	string	The first line for the address	Yes
line_2	string	The second line for the address	No
city	string	The city for the address	Yes
county	string	The county for the address	No
zone	string	The zone code for the address, required for some countries (e.g., US, AU, etc)	Conditional
postcode	string	The postcode for the address, required for some countries (e.g., GB, US, etc)	Conditional
country	string	The country code for the address	Yes
reference	string	The unique reference for the address	No
eori_number	string	The EORI number for the address	No

is_default	boolean	Whether the address is default	No
------------	---------	--------------------------------	----

Example Request

POST /api/customers/{id}/addresses

```
{
  "name": "API Address",
  "first_name": "test",
  "last_name": "test",
  "company": "test",
  "mobile": null,
  "phone": null,
  "line_1": "test",
  "line_2": null,
  "city": "test",
  "county": "Test",
  "zone": null,
  "postcode": "te57 10l",
  "country": "GB",
  "reference": null,
  "eori_number": null,
  "is_default": true
}
```

Example Response

```
{
  "address": {
    "id": 1
  }
}
```

Update Address Endpoint

Structure

Name	Type	Description	Required
<code>id</code>	int	The id for the address	No
<code>name</code>	string	The name of the address	No
<code>first_name</code>	string	The first name for the address	No
<code>last_name</code>	string	The last name for the address	No
<code>company</code>	string	The company for the address	No
<code>mobile</code>	string	The mobile number for the address	No
<code>phone</code>	string	The phone number for the address	No
<code>line_1</code>	string	The first line for the address	No
<code>line_2</code>	string	The second line for the address	No
<code>city</code>	string	The city for the address	No
<code>county</code>	string	The county for the address	No
<code>zone</code>	string	The zone code for the address, required for some countries (e.g., US, AU, etc)	No
<code>postcode</code>	string	The postcode for the address, required for some countries (e.g., GB, US, etc)	No

<code>country</code>	string	The country code for the address	No
<code>reference</code>	string	The unique reference for the address	No
<code>eori_number</code>	string	The EORI number for the address	No
<code>is_default</code>	boolean	Whether the address is default	No

Example Request

```
PUT /api/customers/{id}/addresses/{id}
```

```
{
  "name": "API Address Updated",
  "first_name": "test2",
  "county": "Test 2"
}
```

Example Response

```
{
  "address": {
    "id": 1
  }
}
```

Delete Address Endpoint

Example Request

```
DELETE /api/customers/{id}/addresses/{id}
```

Example Response

```
204 No Content
```