

Manufacturers

- [Manufacturer Index Endpoint](#)
- [View Manufacturer Endpoint](#)
- [Create Manufacturer Endpoint](#)
- [Update Manufacturer Endpoint](#)
- [Delete Manufacturer Endpoint](#)

Manufacturer Index Endpoint

Structure

See [View Manufacturer Endpoint](#) for the structure of the manufacturer payload inside the `data` array.

Example Request

```
GET /api/manufacturers?per_page=2
```

Example Response

```
{
  "current_page": 1,
  "data": [
    //...
  ],
  "first_page_url": "http://aero.test/api/manufacturers?page=1",
  "from": 1,
  "last_page": 3,
  "last_page_url": "http://aero.test/api/manufacturers?page=3",
  "next_page_url": "http://aero.test/api/manufacturers?page=2",
  "path": "http://aero.test/api/manufacturers",
  "per_page": 2,
  "prev_page_url": null,
  "to": 2,
  "total": 5
}
```

See [View Manufacturer Endpoint](#) for the structure of the manufacturer payload inside the `data` array.

View Manufacturer Endpoint

Structure

Manufacturer

Name	Type	Description
<code>name</code>	string	The name of the manufacturer
<code>slug</code>	string	The slug of the manufacturer
<code>reference</code>	string	The reference of the manufacturer
<code>logic</code>	string	The logic of the rules for the manufacturer
<code>logo</code>	object	The logo of the manufacturer, see Image
<code>tags</code>	array	An array of Tag objects
<code>related_manufacturers</code>	array	The related manufacturers of the manufacturer, see Related Manufacturers
<code>rules</code>	array	An array of Listing Page Rule objects
<code>content</code>	object	The Listing Page Content of the category
<code>options</code>	object	The Listing Page Options of the category
<code>seo</code>	object	The SEO of the manufacturer
<code>additional_attributes</code>	array	An array of Additional Attribute objects
<code>settings</code>	object	A Settings object with grouped key-value pairs

Image

Name	Type	Description
<code>url</code>	string	The url of the image

Tag

Name	Type	Description
<code>name</code>	string	The name of the tag (e.g., Small or Red)
<code>group</code>	object	The tag group, see Tag Group

Tag Group

Name	Type	Description
<code>name</code>	string	The name of the tag group (e.g., Size or Colour)

Related Manufacturers

Name	Type	Description
<code>id</code>	int	The id of the manufacturer
<code>name</code>	string	The name of the manufacturer

Rule

Name	Type	Description
<code>type</code>	string	The type of the rule
<code>requirement</code>	string	The requirement of the rule
<code>logic</code>	string	The logic of the rule
<code>data</code>	object	The data for the rule, required keys vary based on <code>type</code> of the rule
<code>data.tags</code>	array	An array of Tag objects for a <code>have_tags</code> rule
<code>data.manufacturers.*.id</code>	int	The manufacturer id for a <code>have_manufacturers</code> rule
<code>data.manufacturers.*.name</code>	string	The manufacturer name for a <code>have_manufacturers</code> rule
<code>data.price_list.id</code>	int	The price list id for an <code>in_price_list</code> rule
<code>data.price_list.name</code>	string	The price list name for an <code>in_price_list</code> rule
<code>data.category.id</code>	int	The category id for an <code>in_category</code> rule
<code>data.category.name</code>	string	The category name for an <code>in_category</code> rule

<code>data.days</code>	int	The days for a <code>published_within_days</code> rule
<code>data.start_at</code>	timestamp	The start at date for a <code>published_within</code> rule
<code>data.end_at</code>	timestamp	The end at date for a <code>published_within</code> rule
<code>data.min_price</code>	float	The min price including tax , in whole units (e.g. pounds not pence) for <code>price_between</code> rule
<code>data.max_price</code>	float	The max price including tax , in whole units (e.g. pounds not pence) for <code>price_between</code> rule
<code>data.currency</code>	string	The currency code for <code>price_between</code> rule

Content

Name	Type	Description
<code>summary</code>	string	The summary content
<code>description</code>	string	The description content
<code>small_image</code>	object	The Small Image
<code>medium_image</code>	object	The Medium Image
<code>large_image</code>	object	The Large Image

Options

Name	Type	Description
<code>categories.mode</code>	string	The category filters mode (e.g., show_all/hide_all/show_some)
<code>categories.values</code>	array	The options for categories on the listings page
<code>categories.values.*.id</code>	int	The id of category
<code>categories.values.*.name</code>	string	The name of category
<code>filters.mode</code>	int	The facet filters mode (e.g., show_all/hide_all/show_some)
<code>filters.values</code>	array	The options for facet filters on the listings page
<code>filters.values.*.name</code>	string	The name of the facet filter, e.g. Manufacturer, Price, etc...
<code>filters.values.*.collapsed</code>	boolean	Whether to collapse the facet filter or not

<code>sort_bys</code>	array	An array of the applied sorts on the listings page (e.g., name-az, name-za, price-low, price-high, etc...)
<code>per_page</code>	int	The per page of the listings page

SEO

Name	Type	Description
<code>heading</code>	string	The SEO Heading
<code>page_title</code>	string	The SEO Page Title
<code>meta_description</code>	string	The SEO Meta Description
<code>canonical</code>	string	The SEO Canonical
<code>noindex</code>	boolean	The SEO No Index
<code>nofollow</code>	boolean	The SEO No Follow

Additional Attribute

Name	Type	Description
<code>key</code>	string	The key of the additional attribute
<code>value</code>	string	The value of the additional attribute

Settings

Settings are grouped as key-value pairs.

- Use "_" for ungrouped settings.
- Each group contains its own object of key-value pairs.

```
{
  "settings": {
    "_": {
      "no_group": "value"
    },
    "group": {
      "key": "value"
    }
  }
}
```

Example Request

GET /api/manufacturers/{id|name}

Example Response

```
{
  "id": 1,
  "name": "Burberry",
  "reference": null,
  "slug": "burberry",
  "logo": {
    "url": null
  },
  "content": {
    "summary": "Listing Page Summary Description",
    "description": "Listing Page Content Description",
    "small_image": {
      "url": null
    },
    "medium_image": {
      "url": null
    },
    "large_image": {
      "url": null
    }
  },
  "tags": [],
  "related_manufacturers": [
    {
      "id": 8,
      "name": "Aztech Mountain"
    }
  ],
  "rules": [],
  "options": {
    "categories": {
      "mode": "show_some",
      "values": [
        {
          "id": 2,
          "name": "Coats"
        }
      ]
    }
  }
}
```

```
    }
  ]
},
"filters": {
  "mode": "show_some",
  "values": [
    {
      "key": "t2",
      "name": "Colour",
      "collapsed": true
    },
    {
      "key": "t1",
      "name": "Size",
      "collapsed": false
    },
    {
      "key": "p",
      "name": "Price",
      "collapsed": false
    },
    {
      "key": "m",
      "name": "Manufacturer",
      "collapsed": false
    },
    {
      "key": "c",
      "name": "Category",
      "collapsed": false
    }
  ]
},
"sort_bys": [
  "model-az",
  "manufacturer-za"
],
"per_page": 2
},
"seo": {
```

```
    "heading": "test heading",
    "page_title": "",
    "meta_description": "",
    "open_graph": "",
    "canonical": "",
    "noindex": 0,
    "nofollow": 0
  },
  "settings": [],
  "additional_attributes": [
    {
      "key": "test_name",
      "value": "test_value"
    }
  ]
}
```

Create Manufacturer Endpoint

Structure

Manufacturer

Name	Type	Description	Required
<code>id</code>	int	The id for the manufacturer	No
<code>name</code>	string	The name of the manufacturer	Yes
<code>slug</code>	string	The slug of the manufacturer, if not present it is auto-generated from name	No
<code>reference</code>	string	The reference of the manufacturer	No
<code>logic</code>	string	The logic of the rules for the manufacturer, and/or (defaults to or if not provided)	No
<code>logo</code>	object	The logo of the manufacturer, see Image	No
<code>tags</code>	array	An array of Tag objects	No
<code>related_manufacturers</code>	array	An array of related manufacturers (ids and/or names)	No
<code>rules</code>	array	An array of Listing Page Rule objects	No
<code>content</code>	object	The Listing Page Content of the manufacturer	No
<code>options</code>	object	The Listing Page Options of the manufacturer	No
<code>seo</code>	object	The SEO of the manufacturer	No

<code>additional_attributes</code>	array	An array of Additional Attribute objects	No
<code>settings</code>	object	A Settings object with grouped key-value pairs	No

Image

Name	Type	Description	Required
<code>src</code>	string	The source url of the image	Yes

Tag

Name	Type	Description	Required
<code>name</code>	string	The name of the tag (e.g., Small or Red)	Yes
<code>group</code>	object	The tag group, see Tag Group	Yes

Tag Group

Name	Type	Description	Required
<code>name</code>	string	The name of the tag group (e.g., Size or Colour)	Yes

Rule

Name	Type	Description	Required
<code>type</code>	string	Rule type. Allowed values: <code>in_category</code> , <code>in_price_list</code> , <code>have_manufacturers</code> , <code>have_tags</code> , <code>price_between</code> , <code>reduced</code> , <code>published_within_days</code> , <code>published_within</code>	Yes
<code>requirement</code>	string	Requirement for the rule. Allowed values: <code>must</code> , <code>must_not</code> . Defaults to <code>must</code>	No
<code>logic</code>	string	How this rule combines with others. Allowed values: <code>and</code> , <code>or</code> . Defaults to <code>or</code>	No

<code>data</code>	object	Rule-specific data (see below). Keys vary depending on type	Yes
<code>data.tags</code>	array	An array of Tag ids (or names formatted as group name). Required if <code>type = have_tags</code>	Conditional
<code>data.manufacturers</code>	array	An array of manufacturer ids (or names). Required if <code>type = have_manufacturers</code>	Conditional
<code>data.price_list</code>	string	Price list id (or name). Required if <code>type = in_price_list</code>	Conditional
<code>data.category</code>	string	Category id (or name/breadcrumb, e.g., Mens > Coats). Required if <code>type = in_category</code>	Conditional
<code>data.days</code>	int	Number of days. Required if <code>type = published_within_days</code>	Conditional
<code>data.start_at</code>	timestamp	The start date. Required if <code>type = published_within</code>	Conditional
<code>data.end_at</code>	timestamp	The end date. Optional if <code>type = published_within</code>	Conditional
<code>data.min_price</code>	float	Minimum price (including tax) in store's default currency, whole units only (e.g. pounds, not pence). Required if <code>type = price_between</code>	Conditional
<code>data.max_price</code>	float	Maximum price (including tax) in store's default currency, whole units only. Required if <code>type = price_between</code>	Conditional

The `rules` are nested within arrays to achieve grouping, see `rules` in Example Request for clarity

Content

Name	Type	Description	Required
<code>summary</code>	string	The summary content	No
<code>description</code>	string	The description content	No

<code>small_image</code>	object	The Small Image	No
<code>medium_image</code>	object	The Medium Image	No
<code>large_image</code>	object	The Large Image	No

Options

Name	Type	Description	Required
<code>categories.mode</code>	string	Categories filter display mode. Allowed values: <code>show_all</code> , <code>hide_all</code> , <code>show_some</code> . Default: <code>show_all</code>	No
<code>categories.values</code>	array	An array of category ids (or names/breadcrumbs, e.g. Mens > Coats) to show. Required if <code>categories.mode = show_some</code>	Conditional
<code>filters.mode</code>	int	Facet filters display mode. Allowed values: <code>show_all</code> , <code>hide_all</code> , <code>show_some</code> . Default: <code>show_all</code>	No
<code>filters.values</code>	array	The options for facet filters on the listings page. Required if <code>filters.mode = show_some</code>	Conditional
<code>filters.values.*.name</code>	string	The name of the facet filter, e.g. <code>Category</code> , <code>Price</code> , etc...	Yes
<code>filters.values.*.collapsed</code>	boolean	Whether to collapse the facet filter or not	Yes
<code>sort_bys</code>	array	An array of the applied sorts on the listings page (e.g., name-az, name-za, price-low, price-high, etc...)	No
<code>per_page</code>	int	The per page of the listings page (defaults to 24)	No

SEO

Name	Type	Description	Required
<code>heading</code>	string	The SEO Heading	No
<code>page_title</code>	string	The SEO Page Title	No
<code>meta_description</code>	string	The SEO Meta Description	No

<code>canonical</code>	string	The SEO Canonical	No
<code>noindex</code>	boolean	The SEO No Index	No
<code>nofollow</code>	boolean	The SEO No Follow	No

Additional Attribute

Name	Type	Description	Required
<code>key</code>	string	The key of the additional attribute	Yes
<code>value</code>	string	The value of the additional attribute	Yes

Settings

Settings are grouped as key-value pairs.

- Use "_" for ungrouped settings.
- Each group contains its own object of key-value pairs.

```
{
  "settings": {
    "_": {
      "no_group": "value"
    },
    "group": {
      "key": "value"
    }
  }
}
```

Example Request

```
POST /api/manufacturers/
```

```
{
  "name": "Burberry 2",
  "slug": "burberry-2",
  "content": {
    "summary": "Listing Page Summary Description",
    "description": "Listing Page Content Description"
  },
}
```

```
"tags": [
  {
    "group": {
      "name": "Size"
    },
    "name": "Small"
  }
],
"related_manufacturers": [
  1
],
"rules": [
  [
    {
      "type": "have_tags",
      "requirement": "must",
      "logic": "or",
      "data": {
        "tags": [
          "size|small"
        ]
      }
    },
    {
      "type": "in_category",
      "requirement": "must",
      "logic": "and",
      "data": {
        "category": 1
      }
    }
  ],
  [
    {
      "type": "in_price_list",
      "requirement": "must",
      "logic": "and",
      "data": {
        "price_list": 1
      }
    }
  ]
]
```

```
    }
  ],
  [
    {
      "type": "price_between",
      "requirement": "must",
      "logic": "and",
      "data": {
        "min_price": 100,
        "max_price": 200
      }
    },
    {
      "type": "reduced",
      "requirement": "must",
      "logic": "and"
    }
  ],
  [
    {
      "type": "published_within_days",
      "requirement": "must",
      "logic": "and",
      "data": {
        "days": "12"
      }
    },
  ],
]
],
"options": {
  "categories": {
    "mode": "show_some",
    "values": [
      1
    ]
  },
  "filters": {
    "mode": "show_some",
    "values": [
      {
```

```
        "name": "Price",
        "collapsed": true
    },
    {
        "name": "Manufacturer"
    }
]
},
"sort_bys": [
    "model-az",
    "manufacturer-za"
],
"per_page": 2
},
"seo": {
    "heading": "test heading",
    "noindex": 0,
    "nofollow": 0
},
"additional_attributes": [
    {
        "key": "test_name",
        "value": "test_value"
    }
]
}
```

Example Response

```
{
  "manufacturer": {
    "id": 1
  }
}
```

Update Manufacturer Endpoint

Structure

Manufacturer

Name	Type	Description	Required
<code>name</code>	string	The name of the manufacturer	No
<code>slug</code>	string	The slug of the manufacturer, if not present it is auto-generated from name	No
<code>reference</code>	string	The reference of the manufacturer	No
<code>logic</code>	string	The logic of the rules for the manufacturer, and/or (defaults to or if not provided)	No
<code>logo</code>	object	The logo of the manufacturer, see Image	No
<code>tags</code>	array	An array of Tag objects	No
<code>related_manufacturers</code>	array	An array of related manufacturers (ids and/or names)	No
<code>rules</code>	array	An array of Listing Page Rule objects	No
<code>content</code>	object	The Listing Page Content of the manufacturer	No
<code>options</code>	object	The Listing Page Options of the manufacturer	No
<code>seo</code>	object	The SEO of the manufacturer	No

<code>additional_attributes</code>	array	An array of Additional Attribute objects	No
<code>settings</code>	object	A Settings object with grouped key-value pairs	No

Image

Name	Type	Description	Required
<code>src</code>	string	The source url of the image	Yes

Tag

Name	Type	Description	Required
<code>name</code>	string	The name of the tag (e.g., Small or Red)	Yes
<code>group</code>	object	The tag group, see Tag Group	Yes

Tag Group

Name	Type	Description	Required
<code>name</code>	string	The name of the tag group (e.g., Size or Colour)	Yes

Rule

Name	Type	Description	Required
<code>type</code>	string	Rule type. Allowed values: <code>in_category</code> , <code>in_price_list</code> , <code>have_manufacturers</code> , <code>have_tags</code> , <code>price_between</code> , <code>reduced</code> , <code>published_within_days</code> , <code>published_within</code>	Yes
<code>requirement</code>	string	Requirement for the rule. Allowed values: <code>must</code> , <code>must_not</code> . Defaults to <code>must</code>	No
<code>logic</code>	string	How this rule combines with others. Allowed values: <code>and</code> , <code>or</code> . Defaults to <code>or</code>	No

<code>data</code>	object	Rule-specific data (see below). Keys vary depending on type	Yes
<code>data.tags</code>	array	An array of Tag ids (or names formatted as group name). Required if <code>type = have_tags</code>	Conditional
<code>data.manufacturers</code>	array	An array of manufacturer ids (or names). Required if <code>type = have_manufacturers</code>	Conditional
<code>data.price_list</code>	string	Price list id (or name). Required if <code>type = in_price_list</code>	Conditional
<code>data.category</code>	string	Category id (or name/breadcrumb, e.g., Mens > Coats). Required if <code>type = in_category</code>	Conditional
<code>data.days</code>	int	Number of days. Required if <code>type = published_within_days</code>	Conditional
<code>data.start_at</code>	timestamp	The start date. Required if <code>type = published_within</code>	Conditional
<code>data.end_at</code>	timestamp	The end date. Optional if <code>type = published_within</code>	Conditional
<code>data.min_price</code>	float	Minimum price (including tax) in store's default currency, whole units only (e.g. pounds, not pence). Required if <code>type = price_between</code>	Conditional
<code>data.max_price</code>	float	Maximum price (including tax) in store's default currency, whole units only. Required if <code>type = price_between</code>	Conditional

The `rules` are nested within arrays to achieve grouping, see `rules` in Example Request for clarity

Content

Name	Type	Description	Required
<code>summary</code>	string	The summary content	No
<code>description</code>	string	The description content	No

<code>small_image</code>	object	The Small Image	No
<code>medium_image</code>	object	The Medium Image	No
<code>large_image</code>	object	The Large Image	No

Options

Name	Type	Description	Required
<code>categories.mode</code>	string	Categories filter display mode. Allowed values: <code>show_all</code> , <code>hide_all</code> , <code>show_some</code> . Default: <code>show_all</code>	No
<code>categories.values</code>	array	An array of category ids (or names/breadcrumbs, e.g. Mens > Coats) to show. Required if <code>categories.mode = show_some</code>	Conditional
<code>filters.mode</code>	int	Facet filters display mode. Allowed values: <code>show_all</code> , <code>hide_all</code> , <code>show_some</code> . Default: <code>show_all</code>	No
<code>filters.values</code>	array	The options for facet filters on the listings page. Required if <code>filters.mode = show_some</code>	Conditional
<code>filters.values.*.name</code>	string	The name of the facet filter, e.g. <code>Category</code> , <code>Price</code> , etc...	Yes
<code>filters.values.*.collapsed</code>	boolean	Whether to collapse the facet filter or not	Yes
<code>sort_bys</code>	array	An array of the applied sorts on the listings page (e.g., name-az, name-za, price-low, price-high, etc...)	No
<code>per_page</code>	int	The per page of the listings page (defaults to 24)	No

SEO

Name	Type	Description	Required
<code>heading</code>	string	The SEO Heading	No
<code>page_title</code>	string	The SEO Page Title	No
<code>meta_description</code>	string	The SEO Meta Description	No

<code>canonical</code>	string	The SEO Canonical	No
<code>noindex</code>	boolean	The SEO No Index	No
<code>nofollow</code>	boolean	The SEO No Follow	No

Additional Attribute

Name	Type	Description	Required
<code>key</code>	string	The key of the additional attribute	Yes
<code>value</code>	string	The value of the additional attribute	Yes

Settings

Settings are grouped as key-value pairs.

- Use "_" for ungrouped settings.
- Each group contains its own object of key-value pairs.

```
{
  "settings": {
    "_": {
      "no_group": "value"
    },
    "group": {
      "key": "value"
    }
  }
}
```

Example Request

```
PUT /api/manufacturers/{id|name}
```

```
{
  "name": "Updated Burberry",
  "slug": "very-burberry",
  "content": {
    "description": "Updated Burberry"
  },
  "seo": {
```

```
    "heading": "Updated Burberry"
  },
  "tags": [
    {
      "name": "Green",
      "group": {
        "name": "Colour"
      }
    }
  ]
}
```

Example Response

```
{
  "manufacturer": {
    "id": 1
  }
}
```

Delete Manufacturer Endpoint

Example Request

```
DELETE /api/manufacturers/{id|name}
```

Example Response

```
204 No Content
```