

Price Lists

- [Price List Index Endpoint](#)
- [View Price List Endpoint](#)
- [Create Price List](#)
- [Update Price List](#)

Price List Index Endpoint

Structure

See [View Price List Endpoint](#) for the structure of the price list payload inside the `data` array.

Example Request

```
GET /api/price-lists?per_page=2
```

Example Response

```
{
  "current_page": 1,
  "data": [
    //...
  ],
  "first_page_url": "http://aero.test/api/price-lists?page=1",
  "from": 1,
  "last_page": 3,
  "last_page_url": "http://aero.test/api/price-lists?page=3",
  "next_page_url": "http://aero.test/api/price-lists?page=2",
  "path": "http://aero.test/api/price-lists",
  "per_page": 2,
  "prev_page_url": null,
  "to": 2,
  "total": 5
}
```

See [View Price List Endpoint](#) for the structure of the price list payload inside the `data` array.

View Price List Endpoint

Structure

Price List

Name	Type	Description
<code>id</code>	int	The id of the price list
<code>name</code>	string	The name of the price list
<code>applies_to</code>	string	The applies to of the price list (e.g., everyone, not-customers, customers, groups)
<code>start_at</code>	timestamp	The start at of the price list
<code>end_at</code>	timestamp	The end at of the price list
<code>entries</code>	array	An array of Entry objects
<code>customer_groups</code>	array	An array of Customer Group objects

Entry

Name	Type	Description
<code>id</code>	int	The id of the price list entry
<code>for</code>	string	What the entry applies to (e.g., all_products, all_products_unless_reduced, product, variant, category, tag, manufacturer)
<code>target</code>	string	Identifier of the target (if applicable) — e.g. product id, variant id, category id, etc...

<code>type</code>	string	Type of price adjustment (e.g., <code>fixed_price</code> , <code>fixed_price_decrease</code> , <code>fixed_price_increase</code> , <code>percentage_decrease</code> , <code>percentage_increase</code>)
<code>price</code>	object	The Price object (only present when <code>type</code> is <i>fixed</i> based)
<code>percentage</code>	float	Percentage value (only present when <code>type</code> is <i>percentage</i> based)
<code>for_price</code>	string	Which price the entry affects (e.g., <code>sale_price</code> , <code>base_price</code> , <code>rrp</code> , <code>cost_price</code>)

Price

Name	Type	Description
<code>amount</code>	float	The price including tax , in whole units (e.g., <code>10</code> = <code>£10</code>)
<code>currency</code>	string	The currency for the price (e.g., GBP)

Customer Group

Name	Type	Description
<code>id</code>	int	The id of the customer group
<code>name</code>	string	The name of the customer group
<code>start_at</code>	timestamp	The start at for the customer group
<code>end_at</code>	timestamp	The end at for the customer group

Example Request

```
GET /api/price-lists/{id}
```

Example Response

```
{
  "id": 1,
  "name": "API Test",
  "applies_to": "everyone",
  "start_at": null,
  "end_at": null,
  "entries": [
    {
      "id": 1,
      "for": "all_products",
      "target": null,
      "type": "fixed_price",
      "price": {
        "amount": 10,
        "currency": "GBP"
      },
      "for_price": "base_price"
    },
    {
      "id": 2,
      "for": "all_products_unless_reduced",
      "target": null,
      "type": "fixed_price_decrease",
      "price": {
        "amount": 10,
        "currency": "GBP"
      },
      "for_price": "base_price"
    },
    {
      "id": 3,
      "for": "product",
      "target": 1,
      "type": "percentage_decrease",
      "percentage": 10,
      "for_price": "sale_price"
    },
    {
      "id": 4,
      "for": "variant",
```

```
    "target": 1,
    "type": "percentage_decrease",
    "percentage": 10,
    "for_price": "sale_price"
  },
  {
    "id": 5,
    "for": "category",
    "target": 1,
    "type": "percentage_decrease",
    "percentage": 10,
    "for_price": "sale_price"
  },
  {
    "id": 6,
    "for": "tag",
    "target": 1,
    "type": "percentage_decrease",
    "percentage": 10,
    "for_price": "sale_price"
  },
  {
    "id": 7,
    "for": "manufacturer",
    "target": 1,
    "type": "percentage_decrease",
    "percentage": 10,
    "for_price": "sale_price"
  }
],
"customer_groups": []
}
```

Create Price List

Structure

Price List

Name	Type	Description	Required
<code>id</code>	int	The id of the price list	No
<code>name</code>	string	The name of the price list	Yes
<code>applies_to</code>	string	The applies to of the price list (everyone, not-customers, customers, groups)	Yes
<code>start_at</code>	timestamp	The start at of the price list	No
<code>end_at</code>	timestamp	The end at of the price list	No
<code>entries</code>	array	An array of Entry objects	No
<code>customer_groups</code>	array	An array of Customer Group objects (only required when <code>applies_to</code> = "groups")	No

Entry

Name	Type	Description	Required
<code>id</code>	int	The id for the entry	No
<code>for</code>	string	What the entry applies to (e.g., all_products, all_products_unless_reduced, product, variant, category, tag, manufacturer)	Yes

<code>target</code>	string	Identifier of the target (e.g., id corresponding to the <code>for</code> or model for product, or sku for variant or name for category/tag/manufacturer)	Conditional
<code>type</code>	string	Type of the price adjustment (e.g., <code>fixed_price</code> , <code>fixed_price_decrease</code> , <code>fixed_price_increase</code> , <code>percentage_decrease</code> , <code>percentage_increase</code>)	Yes
<code>price</code>	object	The Price object (not required when <code>type</code> is <i>percentage</i> based)	Conditional
<code>percentage</code>	float	The percentage of the price list entry (only required when <code>type</code> is <i>percentage</i> based)	Conditional
<code>for_price</code>	string	Which price the entry affects (e.g., <code>sale_price</code> , <code>base_price</code> , <code>rrp</code> , <code>cost_price</code>)	Yes

Price

Name	Type	Description	Required
<code>amount</code>	float	The price including tax , in whole units (e.g., <code>10</code> = <code>£10</code>)	Yes
<code>currency</code>	string	The currency for the price (e.g., GBP)	Yes

Customer Group

Name	Type	Description	Required
<code>id</code>	int	The id of the customer group	Yes
<code>start_at</code>	timestamp	The start at for the customer group	No

end_at	timestamp	The end at for the customer group	No
--------	-----------	-----------------------------------	----

Example Request

POST /api/price-lists

```
{
  "id": 1,
  "name": "API Test",
  "applies_to": "everyone",
  "entries": [
    {
      "for": "all_products",
      "type": "fixed_price",
      "price": {
        "amount": 10,
        "currency": "GBP"
      },
      "for_price": "base_price"
    },
    {
      "for": "all_products_unless_reduced",
      "type": "fixed_price_decrease",
      "price": {
        "amount": 10,
        "currency": "GBP"
      },
      "for_price": "base_price"
    },
    {
      "for": "product",
      "target": 1,
      "type": "percentage_decrease",
      "percentage": 10,
      "for_price": "sale_price"
    },
  ],
}
```

```
{
  "for": "variant",
  "target": 1,
  "type": "percentage_decrease",
  "percentage": 10,
  "for_price": "sale_price"
},
{
  "for": "category",
  "target": 1,
  "type": "percentage_decrease",
  "percentage": 10,
  "for_price": "sale_price"
},
{
  "for": "tag",
  "target": 1,
  "type": "percentage_decrease",
  "percentage": 10,
  "for_price": "sale_price"
},
{
  "for": "manufacturer",
  "target": 1,
  "type": "percentage_decrease",
  "percentage": 10,
  "for_price": "sale_price"
}
],
"customer_groups": []
}
```

Example Response

```
{
  "priceList": {
    "id": 1
  }
}
```


Update Price List

Structure

Price List

Name	Type	Description	Required
<code>name</code>	string	The name of the price list	No
<code>applies_to</code>	string	The applies to of the price list (everyone, not-customers, customers, groups)	No
<code>start_at</code>	timestamp	The start at of the price list	No
<code>end_at</code>	timestamp	The end at of the price list	No
<code>customer_groups</code>	array	An array of Customer Group objects (only required when <code>applies_to</code> = "groups")	No

Customer Group

Name	Type	Description	Required
<code>id</code>	int	The id of the customer group	Yes
<code>start_at</code>	timestamp	The start at for the customer group	No
<code>end_at</code>	timestamp	The end at for the customer group	No

Example Request

```
PUT /api/price-lists/{id}
```

```
{  
  "name": "API Test Updated",  
  "applies_to": "customers"  
}
```

Example Response

```
{  
  "priceList": {  
    "id": 1  
  }  
}
```