Create Address Endpoint

Structure

Name	Type	Description	Required
`id`	int	The id for the address	No
`name`	string	The name of the address	No
`first_name`	string	The first name for the address	Yes
`last_name`	string	The last name for the address	Yes
`company`	string	The company for the address	No
`mobile`	string	The mobile number for the address	No
`phone`	string	The phone number for the address	No
`line_1`	string	The first line for the address	Yes
`line_2`	string	The second line for the address	No
`city`	string	The city for the address	Yes
`county`	string	The county for the address	No
`zone`	string	The zone code for the address, required for some countries (e.g., US, AU, etc)	Conditional
`postcode`	string	The postcode for the address, required for some countries (e.g., GB, US, etc)	Conditional
`country`	string	The country code for the address	Yes
`reference`	string	The **unique** reference for the address	No

`eori_number`	string	The EORI number for the address	No
`is_default`	boolean	Whether the address is default	No

Example Request

```
POST /api/customers/{id}/addresses
```

```
{
    "name": "API Address",
    "first_name": "test",
    "last_name": "test",
    "company": "test",
    "mobile": null,
    "phone": null,
    "line_1": "test",
    "line_2": null,
    "city": "test",
    "county": "Test",
    "zone": null,
    "postcode": "te57 10l",
    "country": "GB",
    "reference": null,
    "eori_number": null,
    "is_default": true
}
```

Example Response

```
{
    "address": {
        "id": 1
    }
}
```

Revision #2
Created 2026-10-01 11:51:52 UTC by Ethan Payne
Updated 2026-10-02 13:25:27 UTC by Ethan Payne