

Create Attribute Group Endpoint

Structure

Attribute Group

Name	Type	Description	Required
<code>id</code>	int	The id for the attribute group	No
<code>name</code>	string	The name of the attribute group (e.g., Size or Colour)	Yes
<code>display_as</code>	string	The display as of the attribute group (e.g.: dropdown, color_swatches, image_swatches, swatches)	No
<code>reference</code>	string	The reference of the attribute group	No
<code>attributes</code>	array	The attributes of the attribute group, see Attribute	No

Attribute

Name	Type	Description	Required
<code>id</code>	int	The id for the attribute	No
<code>name</code>	string	The name of the attribute (e.g., Small or Red)	Yes
<code>display_name</code>	string	The display name of the attribute	No

reference	string	The reference of the attribute	No
image	object	The Image of the attribute	No
tags	array	An array of Tag objects	No

Image

Name	Type	Description	Required
src	string	The source url of the image	Yes

Tag

Name	Type	Description	Required
name	string	The name of the tag (e.g., Small or Red)	Yes
group	object	The tag group, see Tag Group	Yes

Tag Group

Name	Type	Description	Required
name	string	The name of the tag group (e.g., Size or Colour)	Yes

Example Request

POST /api/attribute-groups/

```
{
  "name": "Colour",
  "attributes": [
    {
      "name": "Blue",
```

```
        "reference": "blue"
      },
      {
        "name": "red"
      }
    ]
  }
}
```

Example Response

```
{
  "attributeGroup": {
    "id": 1
  }
}
```

Revision #3

Created 2026-10-01 09:42:45 UTC by Ethan Payne

Updated 2026-10-02 13:17:00 UTC by Ethan Payne