

Create Specification Group Endpoint

This endpoint is only available if `aerocargo/specifications` is installed.

Structure

Specification Group

Name	Type	Description	Required	Version
<code>id</code>	int	The id of the specification group	No	<code>>=0.1.0</code>
<code>name</code>	string	The name for the specification group	Yes	<code>>=0.1.0</code>
<code>sort</code>	int	The sort for the specification group	No	<code>>=1.0.0</code>
<code>fields</code>	array	An array of Field objects	No	<code>>=0.1.0</code>
<code>media</code>	array	An array of Media objects	No	<code>>=0.3.2</code>
<code>settings</code>	object	A Settings object with grouped key-value pairs	No	<code>>=1.0.0</code>

Field

Name	Type	Description	Required	Version
<code>name</code>	string	The name of the field	Yes	<code>>=0.1.0</code>
<code>presets</code>	array	An array of strings to use as preset options	No	<code>>=0.1.0</code>

default	string	The default value for the field, note: _p:0 means the first preset	Yes	>=0.1.0
prefix	string	The prefix for the field	No	>=0.1.0
suffix	string	The suffix for the field	No	>=0.1.0
sort	int	The sort for the field	No	>=1.0.0
media	array	An array of Media objects	No	>=1.0.0
settings	object	A Settings object with grouped key-value pairs	No	>=1.0.0

Media

Name	Type	Description	Required
id	int	The id of the media	*
source	string	The source of the media, e.g. test.png	*

* At least one must be present.

Settings

Settings are grouped as key-value pairs.

- Use "_" for ungrouped settings.
- Each group contains its own object of key-value pairs.

```
{
  "settings": {
    "_": {
      "no_group": "value"
    },
    "group": {
      "key": "value"
    }
  }
}
```

```
    }  
  }  
}
```

Example Request

POST /api/specification-groups/

```
{  
  "name": "API Test",  
  "fields": [  
    {  
      "name": "Field 1",  
      "presets": ["A", "B", "C"],  
      "default": "D",  
      "prefix": "prefix",  
      "suffix": "suffix",  
      "media": [  
        {  
          "id": 1  
        }  
      ],  
      "settings": {  
        "test": {  
          "test": "123"  
        }  
      }  
    }  
  ],  
  "media": [  
    {  
      "id": 1  
    }  
  ],  
  "settings": {  
    "test": {  
      "test": "456"  
    }  
  }  
}
```

```
}  
  }  
}
```

Example Response

```
{  
  "specificationGroup": {  
    "id": 1  
  }  
}
```

Revision #4

Created 2026-10-01 12:33:01 UTC by Ethan Payne

Updated 2026-10-02 13:29:43 UTC by Ethan Payne