

Update Location Endpoint

Structure

Location

Name	Type	Description	Required
<code>id</code>	int	The id for the location	No
<code>name</code>	string	The name of the location	No
<code>email</code>	string	The email of the location	No
<code>phone</code>	string	The phone number for the location	No
<code>line_1</code>	string	The first line for the location	No
<code>line_2</code>	string	The second line for the location	No
<code>city</code>	string	The city for the location	No
<code>county</code>	string	The county for the location	No
<code>zone</code>	string	The zone code for the location, required for some countries (e.g., US, AU, etc)	No
<code>postcode</code>	string	The postcode for the location, required for some countries (e.g., GB, US, etc)	No
<code>country</code>	string	The country code for the location	No
<code>latitude</code>	float	The latitude for the location	No
<code>longitude</code>	float	The longitude for the location	No
<code>opening_hours</code>	object	See Opening Hours	No
<code>additional_attributes</code>	array	An array of Additional Attribute objects	No

Opening Hours

Name	Type	Description	Required
<code>sunday.times</code>	array	An array of Time objects	No
<code>monday.times</code>	array	An array of Time objects	No
<code>tuesday.times</code>	array	An array of Time objects	No
<code>wednesday.times</code>	array	An array of Time objects	No
<code>thursday.times</code>	array	An array of Time objects	No
<code>friday.times</code>	array	An array of Time objects	No
<code>saturday.times</code>	array	An array of Time objects	No
<code>overrides</code>	object	See Overrides	No

Time

Name	Type	Description	Required
<code>start</code>	time	The start of the time range	Yes
<code>end</code>	time	The end of the time range	Yes

Overrides

Name	Type	Description	Required
<code>date</code>	date	The date the override is for	Yes
<code>label</code>	string	The label for the override	No
<code>times</code>	array	An array of Time objects	No

Additional Attribute

Name	Type	Description	Required
<code>key</code>	string	The key of the additional attribute	Yes
<code>value</code>	string	The value of the additional attribute	Yes

Example Request

```
PUT /api/locations/{id|name}
```

```
{
  "opening_hours": {
    "monday": {
      "times": [
        {
          "start": "09:00",
          "end": "12:30"
        },
        {
          "start": "13:00",
          "end": "17:00"
        }
      ]
    },
    "overrides": [
      {
        "date": "2025-12-26",
        "label": "Boxing Day",
        "times": []
      }
    ]
  },
}
```

Example Response

```
{
  "location": {
    "id": 1
  }
}
```

Revision #2

Created 2026-10-01 12:06:45 UTC by Ethan Payne

Updated 2026-10-01 12:08:10 UTC by Ethan Payne