

# View Location Endpoint

## Structure

### Location

| Name                               | Type   | Description                                                                     |
|------------------------------------|--------|---------------------------------------------------------------------------------|
| <code>id</code>                    | int    | The id for the location                                                         |
| <code>name</code>                  | string | The name of the location                                                        |
| <code>email</code>                 | string | The email of the location                                                       |
| <code>phone</code>                 | string | The phone number for the location                                               |
| <code>line_1</code>                | string | The first line for the location                                                 |
| <code>line_2</code>                | string | The second line for the location                                                |
| <code>city</code>                  | string | The city for the location                                                       |
| <code>county</code>                | string | The county for the location                                                     |
| <code>zone</code>                  | string | The zone code for the location, required for some countries (e.g., US, AU, etc) |
| <code>postcode</code>              | string | The postcode for the location, required for some countries (e.g., GB, US, etc)  |
| <code>country</code>               | string | The country code for the location                                               |
| <code>latitude</code>              | float  | The latitude for the location                                                   |
| <code>longitude</code>             | float  | The longitude for the location                                                  |
| <code>opening_hours</code>         | object | See <a href="#">Opening Hours</a>                                               |
| <code>additional_attributes</code> | array  | An array of <a href="#">Additional Attribute</a> objects                        |

### Opening Hours

| Name                      | Type  | Description                              |
|---------------------------|-------|------------------------------------------|
| <code>sunday.times</code> | array | An array of <a href="#">Time</a> objects |

|                              |        |                                          |
|------------------------------|--------|------------------------------------------|
| <code>monday.times</code>    | array  | An array of <a href="#">Time</a> objects |
| <code>tuesday.times</code>   | array  | An array of <a href="#">Time</a> objects |
| <code>wednesday.times</code> | array  | An array of <a href="#">Time</a> objects |
| <code>thursday.times</code>  | array  | An array of <a href="#">Time</a> objects |
| <code>friday.times</code>    | array  | An array of <a href="#">Time</a> objects |
| <code>saturday.times</code>  | array  | An array of <a href="#">Time</a> objects |
| <code>overrides</code>       | object | See <a href="#">Overrides</a>            |

## Time

| Name               | Type | Description                 |
|--------------------|------|-----------------------------|
| <code>start</code> | time | The start of the time range |
| <code>end</code>   | time | The end of the time range   |

## Overrides

| Name               | Type   | Description                              |
|--------------------|--------|------------------------------------------|
| <code>date</code>  | date   | The date the override is for             |
| <code>label</code> | string | The label for the override               |
| <code>times</code> | array  | An array of <a href="#">Time</a> objects |

## Additional Attribute

| Name               | Type   | Description                           |
|--------------------|--------|---------------------------------------|
| <code>key</code>   | string | The key of the additional attribute   |
| <code>value</code> | string | The value of the additional attribute |

## Example Request

```
GET /api/locations/{id|name}
```

## Example Response

```
{
  "id": 1,
  "name": "Aero Commerce",
  "email": null,
  "phone": null,
  "latitude": null,
  "longitude": null,
  "line_1": "28-32 Albert Rd",
  "line_2": null,
  "city": "Middlesbrough",
  "county": null,
  "zone": null,
  "postcode": "TS1 1QD",
  "country": "GB",
  "opening_hours": {
    "sunday": {
      "times": []
    },
    "monday": {
      "times": [
        {
          "start": "07:00",
          "end": "12:00"
        },
        {
          "start": "12:30",
          "end": "15:00"
        }
      ]
    },
    "tuesday": {
      "times": [
        {
          "start": "07:00",
          "end": "12:00"
        },
        {
          "start": "12:30",
          "end": "15:00"
        }
      ]
    }
  }
}
```

```
    ]
  },
  "wednesday": {
    "times": [
      {
        "start": "07:00",
        "end": "12:00"
      },
      {
        "start": "12:30",
        "end": "15:00"
      }
    ]
  },
  "thursday": {
    "times": [
      {
        "start": "07:00",
        "end": "12:00"
      },
      {
        "start": "12:30",
        "end": "15:00"
      }
    ]
  },
  "friday": {
    "times": [
      {
        "start": "07:00",
        "end": "12:00"
      },
      {
        "start": "12:30",
        "end": "15:00"
      }
    ]
  },
  "saturday": {
    "times": []
  }
}
```

```
    },
    "overrides": [
      {
        "date": "2025-12-25",
        "label": "Christmas Day",
        "times": []
      },
      {
        "date": "2025-08-25",
        "label": "Bank Holiday",
        "times": []
      }
    ]
  },
  "additional_attributes": []
}
```

---

Revision #3

Created 2026-10-01 11:59:15 UTC by Ethan Payne

Updated 2026-10-01 12:03:43 UTC by Ethan Payne