

View Specification Group Endpoint

This endpoint is only available if `aerocargo/specifications` is installed.

Structure

Specification Group

Name	Type	Description	Version
<code>id</code>	int	The id of the specification group	<code>>=0.1.0</code>
<code>name</code>	string	The name for the specification group	<code>>=0.1.0</code>
<code>sort</code>	int	The sort for the specification group	<code>>=1.0.0</code>
<code>fields</code>	array	An array of Field objects	<code>>=0.1.0</code>
<code>media</code>	array	An array of Media objects	<code>>=0.3.2</code>
<code>settings</code>	object	A Settings object with grouped key-value pairs	<code>>=1.0.0</code>

Field

Name	Type	Description	Version
<code>name</code>	string	The name of the field	<code>>=0.1.0</code>
<code>presets</code>	array	An array of strings to use as preset options	<code>>=0.1.0</code>

default	string	The default value for the field, note: <code>_p:0</code> means the first preset	<code>>=0.1.0</code>
prefix	string	The prefix for the field	<code>>=0.1.0</code>
suffix	string	The suffix for the field	<code>>=0.1.0</code>
sort	int	The sort for the field	<code>>=1.0.0</code>
media	array	An array of Media objects	<code>>=1.0.0</code>
settings	object	A Settings object with grouped key-value pairs	<code>>=1.0.0</code>

Media

Name	Type	Description
id	int	The id of the media
slug	string	The slug of the media
disk	string	The disk used to store the media
path	string	The path of the media on the disk
title	string	The title of the media
type	string	The mimetype of the media
extension	string	The file extension of the media
size	int	The file size of the media in bytes
meta	object	The meta data of the media
source	string	The source file name of the media
is_protected	bool	Whether the media is protected

Settings

Settings are grouped as key-value pairs.

- Use `"_"` for ungrouped settings.
- Each group contains its own object of key-value pairs.

```
{  
  "settings": {
```

```
    "_": {
      "no_group": "value"
    },
    "group": {
      "key": "value"
    }
  }
}
```

Example Request

```
GET /api/specification-groups/{id}
```

Example Response

```
{
  "id": 1,
  "name": "API Test",
  "fields": [
    {
      "name": "Field 1",
      "presets": ["A", "B", "C"],
      "default": "D",
      "prefix": "prefix",
      "suffix": "suffix",
      "media": [],
      "settings": {
        "test": {
          "test": 123
        }
      }
    }
  ],
  "media": [],
  "settings": {
    "test": {
```

```
    "test": 456
  }
}
```

Revision #5

Created 2026-10-01 12:28:54 UTC by Ethan Payne

Updated 2026-10-02 13:29:32 UTC by Ethan Payne