

What are the available events for the product picker?

Event	Description
products-selected	This event emits when the action button is clicked (bottom right of the modal) and provides an array of all of the selected product(s)/variant(s).
selected	This event emits when the action button is clicked (bottom right of the modal) and is emitted for each product/variant that has been selected - only a single product/variant is provided.

Example

The usual use-case for the Product Picker is to allow users to select products and/or variants to be added to a list. This example code is a Blade view that allows the user to select up to 5 products or variants and then displays them in a list with a custom message. It also allows the user to remove the selected products/variants. The next steps to make this code fully functional would be to wrap the table in a form and to add a submit button that saves the products/variants.

```
@extends('admin::layouts.main')

@section('content')
    <h2>
        <a href="{{ route('admin.modules') }}" class="btn">@include('admin::icons.back')
    Back</a>
    <span class="ml-4">My Module</span>
    </h2>

    <div class="card p-0">
        <table>
            <thead>
```

```

        <tr class="header">
            <th class="whitespace-no-wrap">Model</th>
            <th class="whitespace-no-wrap">Sku</th>
            <th class="whitespace-no-wrap">Message</th>
            <th></th>
        </tr>
    </thead>
    <tbody>
        <tr v-for="(item, index) in list" :key="item.buyable_id + item.buyable_type" v-
cloak>
            <td class="whitespace-no-wrap">
                <input type="hidden" :name="'items[' + index + '][buyable_id]'"
:value="item.buyable_id">
                <input type="hidden" :name="'items[' + index + '][buyable_type]'"
:value="item.buyable_type">
                <span v-text="item.model"></span>
            </td>
            <td class="whitespace-no-wrap" v-if="item.sku" v-text="item.sku"></td>
            <td class="whitespace-no-wrap" v-else><span class="text-grey">—</span></td>
            <td class="whitespace-no-wrap">
                <input type="text" :name="'items[' + index + '][message]'" v-
model="item.message" placeholder="Message">
            </td>
            <td>
                <div class="flex items-center justify-end">
                    <a href="#" @click.prevent="list.splice(index,
1)">@include('admin::icons.bin')</a>
                </div>
            </td>
        </tr>
        <tr v-if="list.length === 0">
            <td colspan="4">No data to show</td>
        </tr>
    </tbody>
</table>

<product-picker v-slot="picker"
v-if="list.length < 5"
get-products-url="{ route('admin.catalog.products.picker') }"
:max-selection="5"
:pick-product="true"

```

```

        :emit-name="true"
        :emit-model="true"
        :emit-sku="true"
        @selected="selected">
        <a href="#" @click.prevent="picker.open" class="btn m-4">Add Product</a>
    </product-picker>
</div>
@endsection

@push('scripts')
<script>
    window.AeroAdmin.addData('list', []);

    window.AeroAdmin.addMethod('selected', function (item) {
        if (this.findIndex(item.buyable_id, item.buyable_type) === -1) {
            this.list.push({
                ...item,
                message: '',
            });
        } else {
            this.$notify({
                type: 'error',
                title: (item.sku ?? item.name) + ' has already been added to the list',
            });
        }
    });

    window.AeroAdmin.addMethod('findIndex', function (id, type) {
        return this.list.findIndex((l) => l.buyable_id === id && l.buyable_type === type);
    });
</script>
@endpush

```

Revision #1

Created 2026-09-02 13:27:23 UTC by Michael Price

Updated 2026-09-02 13:27:23 UTC by Michael Price