

Robots Txt

- [How do I modify robots.txt?](#)

How do I modify robots.txt?

You can modify the `robots.txt` file by extending the `\Aero\Store\Pipelines\RobotsTxt` pipeline.

For example, you can prevent search engines from crawling the admin login page:

```
\Aero\Store\Pipelines\RobotsTxt::extend(function (\Aero\Store\Collections\RobotsTxtCollection
$content, \Closure $next) {
    $adminSlug = config('aero.admin.slug');

    $content->agent('*')->disallow("/{ $adminSlug}");

    return $next($content);
});
```

Parameters

Parameter	Type	Description
<code>\$content</code>	<code>\Aero\Store\Collections\RobotsTxtCollection</code>	The collection of rules for the robots.txt file.
<code>\$next</code>	<code>\Closure</code>	The next step in the pipeline.

Methods

Method	Description
<code>agent(string \$agent)</code>	Gets or creates a new rule collection for the specified user agent.
<code>removeAgent(string \$agent)</code>	Removes a user agent entirely (including all of its defined rules).
<code>allow(string \$value)</code>	Adds an <code>Allow: \$value</code> rule.
<code>removeAllow(string \$value)</code>	Removes an <code>Allow: \$value</code> rule.
<code>disallow(string \$value)</code>	Adds an <code>Disallow: \$value</code> rule.
<code>removeDisallow(string \$value)</code>	Removes an <code>Disallow: \$value</code> rule.
<code>sitemap(string \$value)</code>	Adds an <code>Sitemap: \$value</code> rule.

<code>removeSitemap(string \$value)</code>	Removes an <code>Sitemap: \$value</code> rule.
<code>crawlDelay(string \$value)</code>	Adds an <code>Crawl-delay: \$value</code> rule.
<code>removeCrawlDelay(string \$value)</code>	Removes an <code>Crawl-delay: \$value</code> rule.
<code>requestRate(string \$value)</code>	Adds an <code>Request-rate: \$value</code> rule.
<code>removeRequestRate(string \$value)</code>	Removes an <code>Request-rate: \$value</code> rule.